

MARINEFLEX-TOP-MINI-TW

Cable Entry


INLINE
Cable Entry




LEFT/RIGHT
Cable Entry



REAR
Cable Entry



END CAP



Mounting Profile Information

Accessory: Marineflex Mini Profile
ITEM NO. 44407 - MF-MINI-HS-10X10-1M



Accessory: Marineflex Mini Clip
ITEM NO. 44408 - MF-MINI-CLIP-10X10



Driver Configuration Table

MARINEFLEX-TOP-MINI-TW 9.6W/M			
BC Code	**DRIVER (Non-Dim)**	**SPECIFICATION**	**MARINEFLEX LENGTH**
15210	ORLRPV2435	LED Driver, DC24V, 35W	Up to 3.5M
15214	ORLRPV2460	LED Driver, DC24V, 60W	Up to 5M
	INTERFACE		
34998	ORLDALIIF-12-24-36V-TW-RGBW-DT8	DALI DT8 TW RGBW INTERFACE	Up to 5M

MARINEFLEX-TOP-MINI-TW

Length Matrix

The MARINEFLEX-TOP-MINI-TW can be cut every 41.7mm. The below table gives information on the overall length, obtained by adding the total cable entry length and end mould, to all the available cut lengths up to 5M. **If you require lengths beyond the standard 5M then please contact sales@orlight.com.**

Note: Allow for a tolerance of +/- 0.3mm on cut points.

		Total Length (mm)		
Segments	Luminaire/ Cutpoints	Inline+End	Left/Right+End	Rear+End
1	41.7	58.7	47.7	47.7
2	83.3	100.3	89.3	89.3
3	125.0	142.0	131.0	131.0
4	166.7	183.7	172.7	172.7
5	208.3	225.3	214.3	214.3
6	250.0	267.0	256.0	256.0
7	291.7	308.7	297.7	297.7
8	333.3	350.3	339.3	339.3
9	375.0	392.0	381.0	381.0
10	416.7	433.7	422.7	422.7
11	458.3	475.3	464.3	464.3
12	500.0	517.0	506.0	506.0
13	541.7	558.7	547.7	547.7
14	583.3	600.3	589.3	589.3
15	625.0	642.0	631.0	631.0
16	666.7	683.7	672.7	672.7
17	708.3	725.3	714.3	714.3
18	750.0	767.0	756.0	756.0
19	791.7	808.7	797.7	797.7
20	833.3	850.3	839.3	839.3
21	875.0	892.0	881.0	881.0
22	916.7	933.7	922.7	922.7
23	958.3	975.3	964.3	964.3
24	1000.0	1017.0	1006.0	1006.0
25	1041.7	1058.7	1047.7	1047.7
26	1083.3	1100.3	1089.3	1089.3
27	1125.0	1142.0	1131.0	1131.0
28	1166.7	1183.7	1172.7	1172.7
29	1208.3	1225.3	1214.3	1214.3
30	1250.0	1267.0	1256.0	1256.0
31	1291.7	1308.7	1297.7	1297.7
32	1333.3	1350.3	1339.3	1339.3
33	1375.0	1392.0	1381.0	1381.0
34	1416.7	1433.7	1422.7	1422.7
35	1458.3	1475.3	1464.3	1464.3
36	1500.0	1517.0	1506.0	1506.0
37	1541.7	1558.7	1547.7	1547.7
38	1583.3	1600.3	1589.3	1589.3
39	1625.0	1642.0	1631.0	1631.0
40	1666.7	1683.7	1672.7	1672.7
41	1708.3	1725.3	1714.3	1714.3
42	1750.0	1767.0	1756.0	1756.0
43	1791.7	1808.7	1797.7	1797.7
44	1833.3	1850.3	1839.3	1839.3
45	1875.0	1892.0	1881.0	1881.0

MARINEFLEX-TOP-MINI-TW

orlight®
FROM SOURCE TO SITE

Length Matrix

		Total Length (mm)		
Segments	Luminaire/ Cutpoints	Inline+End	Left/Right+End	Rear+End
46	1916.7	1933.7	1922.7	1922.7
47	1958.3	1975.3	1964.3	1964.3
48	2000.0	2017.0	2006.0	2006.0
49	2041.7	2058.7	2047.7	2047.7
50	2083.3	2100.3	2089.3	2089.3
51	2125.0	2142.0	2131.0	2131.0
52	2166.7	2183.7	2172.7	2172.7
53	2208.3	2225.3	2214.3	2214.3
54	2250.0	2267.0	2256.0	2256.0
55	2291.7	2308.7	2297.7	2297.7
56	2333.3	2350.3	2339.3	2339.3
57	2375.0	2392.0	2381.0	2381.0
58	2416.7	2433.7	2422.7	2422.7
59	2458.3	2475.3	2464.3	2464.3
60	2500.0	2517.0	2506.0	2506.0
61	2541.7	2558.7	2547.7	2547.7
62	2583.3	2600.3	2589.3	2589.3
63	2625.0	2642.0	2631.0	2631.0
64	2666.7	2683.7	2672.7	2672.7
65	2708.3	2725.3	2714.3	2714.3
66	2750.0	2767.0	2756.0	2756.0
67	2791.7	2808.7	2797.7	2797.7
68	2833.3	2850.3	2839.3	2839.3
69	2875.0	2892.0	2881.0	2881.0
70	2916.7	2933.7	2922.7	2922.7
71	2958.3	2975.3	2964.3	2964.3
72	3000.0	3017.0	3006.0	3006.0
73	3041.7	3058.7	3047.7	3047.7
74	3083.3	3100.3	3089.3	3089.3
75	3125.0	3142.0	3131.0	3131.0
76	3166.7	3183.7	3172.7	3172.7
77	3208.3	3225.3	3214.3	3214.3
78	3250.0	3267.0	3256.0	3256.0
79	3291.7	3308.7	3297.7	3297.7
80	3333.3	3350.3	3339.3	3339.3
81	3375.0	3392.0	3381.0	3381.0
82	3416.7	3433.7	3422.7	3422.7
83	3458.3	3475.3	3464.3	3464.3
84	3500.0	3517.0	3506.0	3506.0
85	3541.7	3558.7	3547.7	3547.7
86	3583.3	3600.3	3589.3	3589.3
87	3625.0	3642.0	3631.0	3631.0
88	3666.7	3683.7	3672.7	3672.7
89	3708.3	3725.3	3714.3	3714.3
90	3750.0	3767.0	3756.0	3756.0
91	3791.7	3808.7	3797.7	3797.7
92	3833.3	3850.3	3839.3	3839.3
93	3875.0	3892.0	3881.0	3881.0
94	3916.7	3933.7	3922.7	3922.7

MARINEFLEX-TOP-MINI-TW

Length Matrix

		Total Length (mm)		
Segments	Luminaire/ Cutpoints	Inline+End	Left/Right+End	Rear+End
95	3958.3	3975.3	3964.3	3964.3
96	4000.0	4017.0	4006.0	4006.0
97	4041.7	4058.7	4047.7	4047.7
98	4083.3	4100.3	4089.3	4089.3
99	4125.0	4142.0	4131.0	4131.0
100	4166.7	4183.7	4172.7	4172.7
101	4208.3	4225.3	4214.3	4214.3
102	4250.0	4267.0	4256.0	4256.0
103	4291.7	4308.7	4297.7	4297.7
104	4333.3	4350.3	4339.3	4339.3
105	4375.0	4392.0	4381.0	4381.0
106	4416.7	4433.7	4422.7	4422.7
107	4458.3	4475.3	4464.3	4464.3
108	4500.0	4517.0	4506.0	4506.0
109	4541.7	4558.7	4547.7	4547.7
114	4750.0	4767.0	4756.0	4756.0
115	4791.7	4808.7	4797.7	4797.7
116	4833.3	4850.3	4839.3	4839.3
117	4875.0	4892.0	4881.0	4881.0
118	4916.7	4933.7	4922.7	4922.7
119	4958.3	4975.3	4964.3	4964.3
120	5000.0	5017.0	5006.0	5006.0

NOTE: The max length power from one side is 5 meters. The overall lengths are including Ends, please also allow for +/- 0.3mm Tolerance on overall length. Products are injection moulded by machine that is man operated therefore please allow a tolerance of 5mm.